

CrMo



**3/8" + 1/2" Sensor socket set, 7-pcs.**

**KS TOOLS 150.2100** consists of:

- (A) 150.2122** Oil pressure switch socket dim. 1" and 1-1/16", **extra deep** design (65 mm),  
Length 77 mm, drive: 3/8" square or hexagon, dim. 28 mm, Ford, Opel (GM), Vauxhall and Chrysler
- (B) 150.2123** Thermal switch socket dim. 29 mm for removed and assembly of nearly all switches with plugs or not fixed cable,  
Length 90 mm, drive 1/2", Opel (GM) z.B. Corsa B, Omega, Vectra usw.
- (C) 150.2124** Fuel Injection socket, dim. 27 mm, designed with window for installation and de-installation without damaging the pressure hose,  
Length 85 mm, BMW (eg M21, M41, MSi) and Diesel Engines from Fiat, Ford, VW and Mercedes
- (D) 150.2125** Lambda sensor socket, dim. 22 mm, Slotted recess for electrical cables,  
Height: 48 mm, drive: double 4-square 1/2" for difficult to reach sensors, universal applications
- (E) 150.2126** Lambda sensor socket, dim. 22 mm, **extra flat** design, Slotted recess for electrical cables,  
Height: 31 mm, drive: 3/8", universal applications
- (F) 150.2127** Lambda sensor socket dim. 22, **deep** design, slotted recess for electrical cables,  
Height: 81 mm, drive: 3/8" square or hexagon drive, dim. 26 mm, universal applications
- (G) 150.2128** Lambda sensor socket dim. 22, **extra deep** design, wide recess for electrical cables  
Length: 90 mm, drive: 3/8" square or hexagon dim. 26 mm Mitsubishi, Nissan, GM, VW



**1/2"** Stud puller set, 4-pcs., operate right to left handed

**KS TOOLS 152.1100** consists of:

4 x Stud puller: 6 - 8 - 10 - 12 mm



**1/2"** Stud puller

<b>KS TOOLS</b>	dim.
152.1005	5 mm
152.1006	6 mm
152.1007	7 mm
152.1008	8 mm
152.1010	10 mm
152.1012	12 mm
152.1014	14 mm



**1/2"** Stud puller set, 7-pcs., operate right to left handed

**KS TOOLS 152.1101** consists of:

7 x Stud puller: 5 - 6 - 7 - 8 - 10 - 12 - 14 mm

- Stud screws in and out without using counter nuts on the bolt
- 3 Rollers clamp onto the thread for a sure grip
- Male hexagonal dim. 21 mm male M5 dim. 19 mm
- Through socket for extra long studs

